

Description

Enkasonic Perimeter ISO is a thin, closed cell, foam isolation material for use with Enkasonic Sound Control Matting. The product is extremely flexible and light, making it easy to install and handle. Enkasonic Perimeter ISO is packaged on a roll for long placement runs and limited cutting. It is available in 3 types.

Recommended Applications

- All applications of Enkasonic Sound Control Matting
- At all perimeter walls
- At all floor penetrations such as pipes, conduit and duct work

Technical Data

Packaging

Property	English Units	Metric Units
Product	9003-101-0000	
Roll Width	3.0 in	7.62 cm
Length per Roll	250.0 ft	76.25 m
Total Length	250.0 ft	76.25 m
Rolls per Box	1 roll	
Roll Diameter	36.0 in	91.40 cm
Gross Roll Weight	3.0 lbs	1.36 kg
Thickness	0.25 in	6.35 mm
Color	White	
Adhesive Backing	No	
Minimum Shipment	1 roll	

Property	English Units	Metric Units
Product	9002-025-0880	
Roll Width	2.5 in	6.35 cm
Length per Roll	110.0 ft	33.53 m
Total Length	880.0 ft	268.22 m
Rolls per Box	8 rolls	
Gross Roll Weight	6.0 lbs	5.08 kg
Thickness	0.20 in	6.35 mm
Color	White	
Adhesive Backing	No	
Minimum Shipment	1 box	

Property	English Units	Metric Units
Product	9002-025-A880	
Roll Width	2.5 in	6.35 cm
Length per Roll	110.0 ft	33.53 m
Total Length	880.0 ft	268.22 m
Rolls per Box	8 rolls	
Gross Roll Weight	6.0 lbs	5.08 kg
Thickness	0.20 in	6.35 mm
Color	White	
Adhesive Backing	Yes	
Minimum Shipment	1 box	

Colbond Inc.

PO Box 1057
 Enka, NC 28728
 Telephone 800-365-7391
 Fax 828-665-5009

www.colbond-usa.com

To the best of our knowledge, the information contained herein is accurate. However, Colbond Inc. cannot assume any liability whatsoever for the accuracy or completeness thereof. Final determination of the suitability of any information or material for the use contemplated, of its manner of use and whether the suggested use infringes any patents is the sole responsibility of the user. These products may be covered by patents or patents pending.